

Uniclass L6412	EPIC F32
Cl/SfB	Yq4

April 2006

# Silicone Colour Equalization

Product Datasheet

**EuroMix Dry Mortar System**

## 1. Identification

### 1.1 Introduction

EuroMix Silicone Colour Equalization is a silicone resin specially designed for application onto EuroMix Thin Coat Renders. The product is free of solvents, water resistant, improves the water vapour permeability and scratch-resistance of the façade. EuroMix Silicone Colour Equalization can be applied when colour differences or vandalism to EuroMix Thin Coat Renders occur.

### 1.2 Authority

EuroMix Silicone Colour Equalization is manufactured under a ISO 9001 Quality System.

- Water vapour permeability: SD < 0.1 m to DIN 52615
- Capillary water absorption: W24 , 0.1 (kg/m<sup>2</sup>/H0.5) to DIN 52617
- pH 8.0 +/-1.0
- Density: g/m<sup>3</sup> 1.5 +/-0.1
- Finish: Matt

### 1.3 General Advantages

- Solvent free, environmental friendly, low odour
- Water resistant and micro porous
- Covers in one application
- Quick drying

### 1.4 Application

EuroMix Silicone Colour Equalization is ready to use, stir well before use. It can be applied 48 hours after application of EuroMix Thin Coat Renders. The product can be applied by roller and brush at temperatures between +5°C and +30°C in the same colour as the render. The substrate must be dry, free of dust and loose material. Entire panel must be painted rather than patch painting to ensure uniformity.

## 2. Description

### 2.1 Manufacture

Raw materials and end products are subject to regular quality control procedures and testing. Materials are weighed and mixed under computer control with rigorous quality assurance procedures.

### 2.2 Colours

EuroMix Silicone Colour Equalization is available in matching colours to the EuroMix Thin Coat Renders.

## 3. Performance

EuroMix Silicone Colour Equalization is formulated to give optimum workability. When dried this product gives excellent durability with resistance to scratching, rain penetration and weathering.

## 4. Prices and Conditions of Sale

Our Sales Office will be pleased to provide quotations for specific projects. All quotations are subject to our Conditions of Sale - a copy of which is available on request.

## 5. Supply


EuroMix Silicone Colour Equalization is available throughout the market area of each plant. EuroMix Silicone Colour Equalization is delivered in 15 litre buckets. Approximate yields are shown below: 0.30 litre per m<sup>2</sup>

## 6. Technical Services

Our Technical Advisory Service is available to give expert advice on the specification or use of EuroMix Silicone Colour Equalization.



**EuroMix**



Helpline: **0845 850 9090** (UK) **01 630 2732** (Ireland)

Visit us at: **[www.euromix.com](http://www.euromix.com)**

E-mail: **[info@cpieuromix.com](mailto:info@cpieuromix.com)**



FM 60139

